

JORDAN AND HAMBURG LLP
122 East 42nd Street
New York, NY 10168
Tel: (212) 986-2340
Fax: (212) 953-7733

1617 Rec'd PCT/PTO 20 JUN 2001
09/868688

Docket No. F-7028
Date June 20, 2001

"EXPRESS MAIL" MAILING LABEL NO. EL 666237508US

DATE OF DEPOSIT June 20, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D. C. 20231.

Madeline Gonzalez

(Typed or printed name of person mailing paper or fee)

Madeline Gonzalez
(Signature of person mailing paper or fee)

THE ASSISTANT COMMISSIONER FOR PATENTS
Washington, D. C. 20231

[] ATTN: BOX PATENT APPLICATION
[X] ATTN: BOX PCT

[X] THIS IS THE NATIONAL STAGE OF PCT/DE99/04029 FILED December 17, 1999

Sir:

Transmitted herewith for filing is the [X] Utility [] Design patent application of:

Inventor/Application Identifier: Klaus FISCHER et al.

For: ORGANIC FERTILIZER HAVING HUMIC PROPERTIES,
ITS METHOD OF PRODUCTION AND ITS USE

Enclosed are:

- [] sheets of drawings ([] formal [] informal size A4).
[X] 10 pages of specification, including claims and abstract.
[X] 10 total pages
[] Combined Declaration/Power of Attorney
[] Newly executed
[] Copy from prior application
[] Inventors deleted; see attached statement
[X] Inventor Information Sheet
[] Incorporation By Reference. The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein
[] Sequence Listing
[] Computer Readable Copy
[] Paper copy
[] The undersigned hereby affirms that the content of the paper and computer readable copies of the Sequence Listing are the same.
[] Cancel in this application original claims _____ of the prior application before calculating the filing fee.

CLAIMS FILED

For	Number Filed	Number Extra	Rate	Basic Fee \$860.00
Total Claims	20	(over 20)	x \$ 18.00	
Independent Claims	1	(over 3)	x \$ 80.00	
[X] Multiple Dependent Claim			\$ 270.00	\$270.00
[] Reduce by 50% for Small Entity			-	
[] Foreign Language Filing Fee			\$130.00	

TOTAL FILING FEE \$1,130.00

[X] Please charge Deposit Account No. 10-1250 in the amount of
A duplicate copy of this sheet is attached.

\$1,130.00.

[X] Please charge to Deposit Account No. 10-1250 any further fees under
37 CFR 1.16; 37 CFR 1.17; 37 CFR 1.492.


- [X] Return Receipt Postcard
- [X] Preliminary Amendment
- [] Assignment to _____.
- [] Assignment is of record in prior application Serial No. _____.
- [] Assignment Recordation Form Cover Sheet.
- [] Charge \$40.00 to Deposit Account No. 10-1250 for recording Assignment.
- [X] Information Disclosure Statement and/or Information Disclosure Citation
- [] English translation
- [] Small Entity Status is asserted.
- [] Applicant hereby claims the benefit of the filing date of the following provisional application(s) under the provisions of 35 USC 119.
- [X] Applicant hereby claims the benefit of the filing date of the following applications under the provisions of 35 USC 119 of which certified copies [] will follow [] are enclosed [X] have been filed in the International Bureau [] were filed in prior application No. _____.

German Patent Appln. No. 198 59 068.7, filed December 22, 1998.

- [] This is a [] Continuation [] Divisional [] Continuation-in-Part of prior application Serial No. _____.
- [] Amend the specification by inserting before the first line the sentence:
--This is a [] continuation, [] division, [] continuation-in-part, of application Serial No. _____, filed _____, --

JORDAN AND HAMBURG LLP

By



C. Bruce Hamburg
Reg. No. 22,389
Attorney for Applicants

F-7028

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Klaus FISCHER et al.
Serial No. : Not yet known (U.S. National Stage of PCT/DE99/04029
filed December 17, 1999)
Filed : Concurrently herewith
For : ORGANIC FERTILIZER HAVING HUMIC PROPERTIES, ITS
METHOD OF PRODUCTION AND ITS USE

Assistant Commissioner for Patents
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Sir:

Preliminary to examination, please amend this application as follows:

IN THE CLAIMS:

Cancel claims 1-10 and substitute therefor the following claims:

--11. A method for the production of organic fertilizer of humic-like nature, comprising suspending lignite in an aqueous-ammoniacal medium of pH greater than about 9 and up to about 12, dissolving partially and oxidizing the lignite at a temperature of about 20 to about 100°C under atmospheric pressure thereby to obtain the organic fertilizer as a dispersion in aqueous medium and thickening or drying the dispersion, the organic fertilizer having a C/N ratio of about 9 to about 15.

12. The method according to claim 11, wherein the aqueous-ammoniacal medium is a

mixture of a suspension and a solution, the mixture containing the lignite is introduced into a reactor and, without the supplying of air or oxygen to the reactor, is activated alkaline and within a period of up to about 0.5 hour is heated to an oxidation temperature of below 100°C whereupon oxidizing gas comprising air or oxygen or mixtures thereof is injected into the mixture, the oxidizing gas being at atmospheric pressure and the mixtures of air and oxygen having oxygen partial pressures of about 0.02 to less than 0.1 MPa, terminating the injection of the oxidizing gas and cooling the mixture.

13. The method according to claim 11 or 12, in which the oxidation is effected by contacting the lignite with air or oxygen or a mixture of air and oxygen and the ammonia concentration of the aqueous ammoniacal medium is up to about 7%.

14. The method of claim 11 or 12, wherein the lignite is particulate.

15. The method of claim 11 or 12, wherein the oxidizing is effected over a period of about 0.25 to about 4 hours.

16. The method of claim 11 or 12, wherein the lignite is in admixture with at least one substance selected from the group consisting of lignins from pulp-making, lignins from wood hydrolysis, lignocellulose from steam explosion pulping for the production of fibrous materials, wood particles and bark particles.

17. The method of claim 11 or 12, further comprising a step of adding a macro or micro nutrient thereby to incorporate the nutrient in the fertilizer.

18. The method of claim 17, wherein the nutrient is phosphorous.

19. An organic fertilizer of humic-like nature prepared by the method of claim 11 or 12 having a C/N ratio of about 9 to about 15 wherein various proportions of the nitrogen are chemically bonded as follows,

20-45% as ammonium nitrogen and

55-80% organically bonded,

of said organically bonded nitrogen,

up to 20% being organically bonded as amide, and

up to 80% being organically bonded more strongly than amide.

20. The organic fertilizer according to claim 19, wherein the nitrogen content is up to about 6%.


21. A method of improving the crop yield and quality of soil, comprising applying the fertilizer of claim 19 thereto.

REMARKS

The present amendment is directed to formalities for better conforming the claims to U.S. practice.

Respectfully submitted,

JORDAN AND HAMBURG LLP

By 
C. Bruce Hamburg
Reg. No. 22,389
Attorney for Applicants

122 East 42nd Street
New York, New York 10168
(212) 986-2340

Organic fertiliser of humus-like nature as well as process of its production, and use

Specification

The invention concerns a method for the production of an organic fertiliser of humic-like nature according to the generic term of Claim 1. The invention refers furthermore to a fertiliser of a special composition as well as its use, produced according to the process. The fertiliser can be used as a close-to-nature material for sustainable plant nutrition and soil improvement.

Owing to its properties and its availability lignite has already for long aroused the interest taken in the production of substances or mixtures of substances being effective as fertilisers

So from DE 22 47 938 A a process according to the generic term of Claim 1 is known. Raw lignite is oxidised and ammoniated in aqueous suspension at increased temperature (80 to 200°C) and a raised pressure (up to 50 at plus pressure). The suspension contains 95 to 70 per cent by weight water, ammonia is added, heated to conversion temperature in a pressure vessel which then is brought to conversion pressure by injecting pure oxygen. A particular mode of adjustment to a definite pH value is not described.

From the EP 0 298 710 a process is known, according to which coal is processed based on aqueous medium to obtain a suspension of a 4 to 9 pH. The suspension is oxidised by means of a gaseous oxidant such as oxygen, air and mixtures thereof. The oxidation takes place at temperatures from 100 to 300°C under a pressure of 0.1 to 10 MPa and during a reaction time of 5 to 600 minutes. The oxidised product appears to have a nitrogen proportion just below 2 %. This results in an unfavourable C/N ratio of approximately 35 up to 40.

A procedure to stimulate the growth of seedlings is known from DE 40 15 277 A1, characterised by application of a coal oxidation product to the growing medium of the seedling. A product is suggested as coal oxidation product which is obtained by dry oxidation of the coal with oxygen, particularly air, at a temperature between 120 and 350°C and an oxygen partial pressure between 0.01 and 1 MPa, preferably between 0.01 and 0.5 MPa, over a time of contact between 15 and 600 minutes. A product is suggested as another coal oxidation product, which is produced according to EP 0 298 710. Typically, the coal oxidation product resulting from dry oxidation is characterised by a nitrogen proportion of less than 2% and a C/N ratio of about 35.

According to US 3 607 212, lignite is mixed with inorganic substances and/or organic bulk waste. If appropriate, these mixtures are subjected to a preliminary mechanical treatment and/or to hydrolytic processes.

Other known papers also refer to the high proportion of coal humic acids contained in lignite and the possibilities of obtaining them. For example, the coal humic acids were extracted according to US 3 770 411, using aqueous ammonia, and the extracts converted by means of phosphoric acid.

A process is known from the US 4 013 440 by which coal is directly treated with urea or urea solutions and the products of which being subsequently oxidised by means of HNO₃ and H₂O₂, respectively.

In Mukherjee, P.N. et al: Proc. Nat. Acad. Sci. India, Vol. A 38, 1961, Nr. 1, pp. 124-126 the target was pursued to produce, in a direct way from coal, organic-mineral fertilisers with a high nitrogen content (10...20%). In the process described the conversion of coal by means of ammonia/air/oxygen mixtures is referred to, however in fluid process, at temperatures ranging from 250 to 325° C, by the principle of amoxydation.

Furthermore, from the printed script Gürüz; Kemal: Oxy-ammoniation of Elbistan lignite to produce a nitrogenous fertiliser, Fuel, 1980, Vol. 59, pp. 772 - 776 investigations have become known in which a definite lignite was converted using aqueous ammonia and oxygen at increased pressure in an autoclave at raised temperatures. The oxygen pressure, measured at 25°C occurred in orders of magnitude ranging from 0.1 to 2.3 MPa. To achieve a high N content, the lignite was pre-treated using mineral acids. The product generated in this way has a total nitrogen content of 8.8 to 18%, with up to 64% being available as water-soluble proportions in the form of ammonium. This fertiliser may be assessed as a pure nitrogen fertiliser characterised by a high proportion of ammonium.

Yet another process for producing an organic fertiliser by oxidative ammonolysis of technical lignin is known from EP 0 689 526 B 1, with lignin being isolated by precipitation from waste liquors of alkaline chemical pulping processes and from alkaline lignin extractives. A special characteristic of the process is that the precipitation of lignin is completed in the alkaline environment. The organic fertiliser is distinguished by a particularly high proportion of stronger organically bonded nitrogen (55% to 85% of total nitrogen of the fertiliser). The have the process run requires the presence of freely available technical lignin.

The objective of the invention consists in converting, based on application of a process, an organic substance occurring plentifully in nature into an organic fertiliser characterised by pronounced humic properties, an increased nitrogen content, with the C/N ratio being favourable and a slow-release fertilising effect.

Pertaining to the invention this objective is implemented in that lignite is suspended in an aqueous ammoniacal milieu of pH > 9 up to 12 and in this connection is partially dissolved and in aqueous ammoniacal medium oxidised at a temperature from 20°C to 100°C under normal pressure; and the organic fertiliser is obtained as a dispersion in aqueous medium, by thickening, or drying with the C/N ratio being between 9 to 15.

The peculiarity of the process is that the lignite in terms of a mixture of an aqueous suspension and solution in alkaline medium is mildly oxidised in the presence of a N-basic reactant like, in particular, ammonia.

In an advantageous variant of the process, lignite is at first transferred into an aqueous-ammoniacal mixture of suspension and solution, and in the following activated in alkaline medium in a reactor being designed by the injector principle, for the time being without any supply of oxygen/air, and in this connection heated to the oxidation temperature during a time period adjustable to up to 0.5 h. So as to obtain a mild, however effective oxidation already at a relatively low reaction temperature of far below 100°C, the next step consists in charging the oxidising gas into the reaction mixture via the injector. This process results in the emergence of a system consisting of liquid and fine-bubbly foam being characterised by a large exchange area between the organic substance in the liquid and the oxidising gas. This enables to bring about the effective oxidation both by oxygen and also by air and in the latter case at a

remarkably lower oxygen partial pressure of far below 0.1 MPa as compared with the application of pure oxygen.

When the given time of reaction has elapsed, the oxygen input is switched off and the reaction is stopped. This is followed by the cooling down of the reaction mixture without further oxygen supply to a temperature which is required for a processing. In this context, the special reactor advantageously facilitates the cooling down periods to last for as short a period as < 1h.

The oxidation can be carried out in the presence of air or oxygen, or air/oxygen mixtures and in an aqueous-ammoniacal medium at an ammonia concentration of up to 7%. Lignite of various particle sizes can be used.

Advantageously the oxidation is run at a reaction temperature of up to 100 °C and over a time period of 0.5 to 4 hours.

Corresponding to the special execution of the process, use is made of the starting material lignite in a mixture with technical lignins from pulp making industry as well as from wood hydrolysis, lignite in a mixture with lignin as well as lignocellulose material from the Steam Explosion pulping used in the manufacture of fibrous materials, as well as lignite in a mixture with lignocellulose material such as wood or bark particles.

Another advantageous execution of the process envisages that subsequent to the oxidation of lignite or of lignite in a mixture with lignins another addition with macro and micro nutrients such as phosphorus is performed.

An organic fertiliser obtained from this process is characterised by the features named in claim 8. The fertiliser pertaining to the invention is distinguished by a C/N ratio from 9 to 15, with the nitrogen occurring in different forms of bond.

The use of the organic fertiliser is described by the features named in claim 10.

Surprisingly, in this process lignite, although containing a high proportion of structures of the coal-specific kind of humic and fulvic acids which are a highly condensed, suspended or partially dissolved in an aqueous ammoniacal medium by oxidation is convertible into a humus-like fertiliser characterised by a slow-release effect. In the process pertaining to the invention nitrogen in chemically bonded form is introduced into the coal humic substances, causing the chemical structure of the coal humic substances to change into a form greatly resembling the humic substances typical of soil emerging under natural conditions. At the same time, the high-molecular organic structures of the coal which are not similar to humic substances are partially decomposed, i.e. broken down into smaller molecular sizes, and modified by polar groups.

The process can be technologically implemented by keeping the aqueous ammoniacal mixture of suspension and solution of the starting material in circulation via a heat exchanger, whilst charging the oxidising gas via an injector system.

Compared with previous solutions, this process comprises a number of advantages. It is distinguished by the fact that lignite as starting material, is converted as a whole without preceding separating operations and the humic substitute produced in the conversion can equally be utilised as a whole product without requiring additional separation processes.

Oxygen or air alone may serve as oxidant. In contrast to all previously described processes of an oxidation of this kind by means of oxygen or air, the oxidant is advantageously applied, pertaining to the invention, under mild conditions at normal pressure and at temperatures of up to 100°C.

The products made from lignite by this process may contain as much as 6% of total nitrogen occurring in diverse types of chemical bond which differ by their hydrolyzability. The nitrogen bonded in terms of ammonium (20-45% of total nitrogen), can by means of MgO suspended in water readily be cleaved off in terms of ammonia, whereas the organic kinds of bond (55 - 80% of total nitrogen) are not readily hydrolyzable. A part of the organically bonded nitrogen occurs in terms of amide (up to 20% of total nitrogen) which hydrolyse in the normal manner by means of diluted sodium hydroxide solution under the conditions of steam distillation. That portion which is non-hydrolyzable under these experimental conditions is designated as stronger organically bonded nitrogen (up to 60% of total nitrogen).

These various kinds of bond of nitrogen together with the organic matrix cause the plants to be provided with nitrogen in a lasting and slow release manner. This goes along with a remarkable reduction in nitrogen leaching to seepage and ground-water.

As a whole, the elementary-analytical data of the products reveal the favourable and desired modifications of the starting material, which are achieved by this process.

The high C/N ratio of 93 of the starting lignite could be decreased to the value of 9 - 15

- a value being advantageous for the application.

There is an increase of the atomic H/C ratio from 1.05 to 1.28. While in the coal humic acids, approx. 1 - 1.5% of N appear to be organically bonded, this proportion in the humic substitutes accounts for up to 4%, which is similar to the humic acids of the soil which forming under natural conditions.

The process pertaining to the invention enables lignite from various sites (origin) to be used as starting material.

It is a particular advantage of the process that mixtures of lignite with technical lignins from pulp-making as well as wood hydrolysis, of lignite with lignin as well as lignocellulose material from the Steam Explosion pulping for the production of fibrous material, and from lignite with lignocellulose material such as wood and bark particles, respectively, can likewise be used as starting material.

By application of the above mentioned mixtures, product properties are attainable which facilitate effective special applications like e.g. the prevention of erosion. Moreover, the process pertaining to the invention is characterised by the possibility to also add to the product macro and micro nutrients such as phosphorus.

Subsequently, the invention will be described in closer detail by examples.

Example 1

30 - 70 g of lignite of a particle size within the range of < 1.0 mm, preferably < 0.4 mm, were suspended in 200 - 300 ml of ammonia by thorough mixing and, in this context, partly dissolved. Next, this mixture consisting of suspension and solution was filled in a reactor, while adding 3000 - 3500 ml of ammonia.

In a second variant, this mixture of suspension and solution was pre-treated by allowing it to stand for several hours with occasional shaking and intermixing. This is followed by the process corresponding to variant 1.

Subsequently, the mixture is circulated via a tube reactor and a heat exchanger, with a reaction temperature being adjusted to 70 - 76°C. After assuming the given reaction temperature, oxygen is charged at a rate of 30 - 50 L/h via an injection system and the beginning oxidative

ammonolysis takes place under continuous circulation and a steady supply of the oxidising gas over a reaction period from 1 to 4 hours.

When the reaction is completed, the oxygen supply is switched off, the reaction mixture cooled down by circulation, and subsequently discharged. Finally, following evaporation or vacuum evaporation, respectively, the reaction product is obtained in terms of a solid.

The nitrogen yield was determined analytically.

Elementary analysis:

C	53.50 %
H	5.32 %
N	5.97 %
S	0.45 %

Types of bond of nitrogen (in % of total nitrogen content):

ammonium-N	32.8 %
organically bonded	67.2%
amide-N	11.1 %
stronger organically bonded	56.1 %

Example 2

The conversion takes place like in Example 1, variant 1 or 2. Instead of oxygen, however, air, is charged as oxidising gas at a rate of 50 L/h.

The nitrogen yield was analytically determined.

Elementary analysis:

C	57.03 %
H	5.15 %
N	5.56 %
S	0.58 %

Types of bond of nitrogen (in % of total nitrogen content):

ammonium-N	34.6 %
organically bonded	65.4 %
amide-N	14.0 %
stronger organically bonded	51.4 %

Example 3

35 g of lignite of particle sizes within the range < 1.0 , preferably < 0.4 mm, were suspended in 200 ml of ammonia by thorough intermixing, and partly dissolved, and 35 g of alkali lignin dissolved in 200 ml of ammonia. The mixture consisting of coal suspension and solution and the lignin solution were put together and further processed either immediately as described in Example 1, variant 1, or subsequent to a pre-treatment as described in Example 1, variant 2.

This was followed by filling this whole mixture in the reactor, while adding 3000 to 3500 ml of ammonia.

Subsequently, the mixture was circulated via a tube reactor and a heat exchanger and adjusted to the reaction temperature of 70 - 76 °C.

The nitrogen yield was determined analytically.

Elementary analysis:

C	55.92 %
H	5.46 %
N	5.56 %
S	0.86 %

Types of bond of nitrogen (in % of total nitrogen content):

ammonium-N	35.3 %
organically bonded	64.7 %
amide-N	11.5 %
stronger organically bonded	53.2 %

Example 4

35 g of lignite of the particle sizes within the range of < 1.0 , preferably < 0.4 mm, were suspended in 200 ml of ammonia by thorough intermixing and partly dissolved, and 35 g of dry powdery sulphite spent liquor were dissolved in 200 ml of ammonia. The mixture consisting of coal suspension and solution and the lignin solution were mixed and further processed either immediately as described in Example 1, variant 1, or subsequently to a pre-treatment as described in Example 1, variant 2.

Next, the whole mixture was filled in the reactor, while adding 3000 - 3500 ml of ammonia.

This was succeeded by circulating the mixture via a tube reactor and a heat exchanger and adjusting the reaction temperature to 70 - 76 °C.

The nitrogen yield was analytically determined.

Elementary analysis:

C	45.97 %
H	4.94 %
N	4.65 %
S	3.86 %

Types of bond of nitrogen (in % of total nitrogen content):

ammonium-N	35.9 %
organically bonded	64.1 %
amide-N	14.6 %
stronger organically bonded	49.5 %

Example 5

The conversion was performed as in Example 4. Instead of oxygen, however, air was charged as oxidising gas at a rate of 50 L/h.

The nitrogen yield was analytically determined.

Elementary analysis:

C	49.77 %
H	4.73 %
N	3.34
S	3.55 %

Types of bond of nitrogen (in % of total nitrogen content):

ammonium-N	31.1 %
organically bonded	68.9 %

Claims

Claim 1

A method for the production of an organic fertiliser of humic-like nature, by oxidising and ammoniating treatment of lignite, characterised by the fact that the lignite is suspended in an aqueous-ammoniacal medium of pH > 9 up to 12 and is partly dissolved and is oxidised at a temperature from 20 to 100°C under normal pressure; and the organic fertiliser is obtained as a dispersion in aqueous medium, by thickening, or drying, with the C/N ratio being between 9 to 15.

Claim 2

A process according to claim 1, characterised by the fact that lignite is transferred into an aqueous ammoniacal mixture of a suspension and solution, and afterwards in a reactor in the first place without supply of oxygen or air is activated alkaline and heated within in an adjustable time span of up to 0.5 hour to an oxidation temperature of below 100°C, and subsequently the oxidising gas at a reaction temperature below 100°C, in terms of air or oxygen under normal pressure, and in terms of air/oxygen mixtures under normal pressure with an oxygen partial pressure in the range between 0,02 and < 0.1 MPa, is introduced into the reaction mixture by the injector principle, and finally the supply of oxidising gas is shut and the reaction stopped and the reaction mixture without any continued charging of oxidising gas cooled down in a time period of less than one hour to a temperature required for further processing.

Claim 3

A process according to claim 1 or 2, characterised by the fact that the oxidation with air or oxygen, or air/oxygen mixtures is carried out in an aqueous-ammoniacal mixture of suspension and solution with an ammonia concentration of up to 7 %.

Claim 4

A process according to one or several of claims 1 to 3, characterised by the fact that lignite of various particle sizes is used.

Claim 5

A process according to one or several of the claims 1 to 4, characterised by the fact that the oxidation is carried out over a period from 0.25 to 4 hours.

Claim 6

A process according to one or several of the claims 1 to 5, characterised by the fact that lignite as mixed with technical lignins from pulp-making, or as mixed with technical lignins from wood hydrolysis, or as mixed with lignin or with lignocellulose material from the Steam Explosion pulping for the production of fibrous materials, and lignite as mixed with lignocellulose material such as wood and bark particles, can be used.

Claim 7

A process according to one or several of claims 1 to 6, characterised by the fact that macro and micro nutrients such as phosphorus can be added during or subsequent to the oxidation of lignite or lignite in a mixture containing lignins.

Claim 8

An organic fertiliser of humic-like nature according to one of the claims 1 to 7, characterised by the fact that the product has a C/N ratio from 9 to 15, and that nitrogen occurs in various chemical bonds as compared with total nitrogen, of which

- 20 - 45 % are available in terms of ammonium nitrogen
- 55 - 80 % are organically bonded, of which
- up to 20 % of the total nitrogen are bonded in terms of amide, and
- up to 60 % occur in terms of stronger organic bonds

Claim 9

Organic fertiliser according to Claim 8, characterised by the fact that in a C/N ratio from 9 to 15 the organic fertiliser contains up to 6% total nitrogen.

Claim 10

Use of the organic fertiliser according to one or several of the claims 1 to 9, characterised by the fact that the organic fertiliser is applied as such or is added to substrates of yield improving and soil ameliorating properties.

Abstract

Organic fertiliser of humic-like nature as well as process of its production, and use

The invention concerns a method for the production of an organic fertiliser of humic-like nature, by oxidising and ammoniating treatment of lignite, characterised by the fact that lignite is suspended in an aqueous ammoniacal medium of pH > 9 to 12 and in this context is partially dissolved and is oxidised at a temperature of 20 - 100°C at normal pressure; and the organic fertiliser being obtained as a dispersion in aqueous medium, by thickening, or by drying, with a C/N ratio from 9 to 15. An organic fertiliser as well as its use is described. The process enables the production of an organic fertiliser from lignite distinguished by a humus-like structure and slow-releasing fertilisation effect, and its use as such or as an addition to yield-increasing and soil-ameliorating substrates.

**COMBINED DECLARATION FOR PATENT APPLICATION AND
POWER OF ATTORNEY**

(Includes Reference to PCT International Applications)

Attorney's Docket Number

F-7028

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

ORGANIC FERTILIZER HAVING HUMIC PROPERTIES, ITS

METHOD OF PRODUCTION AND ITS USE

the specification of which (check only one item below):

☐ is attached hereto.

☐ was filed as United States application

Serial No. _____

on _____,

and was amended

on _____ (if applicable).

☒ was filed as PCT international application

Number PCT/DE99/04029,

on December 17, 1999

and was amended under PCT Article 19

on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

PRIOR FOREIGN/PCT APPLICATION(S) AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. 119:			
Country (if PCT indicate "PCT")	Application Number	Date of Filing (day, month, year)	Priority Claimed Under 35 USC 119
Germany	198 59 068.7	22, December 1998	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
			<input type="checkbox"/> Yes <input type="checkbox"/> No
			<input type="checkbox"/> Yes <input type="checkbox"/> No
			<input type="checkbox"/> Yes <input type="checkbox"/> No
			<input type="checkbox"/> Yes <input type="checkbox"/> No

COMBINED DECLARATION FOR PATENT APPLICATION AND
POWER OF ATTORNEY (Continued)
(Includes Reference to PCT International Applications)

Attorney's Docket Number

F-7028

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:					
U.S. APPLICATIONS			STATUS (Check One)		
U.S. Application Number	U. S. Filing Date		Patented	Pending	Abandoned
PCT APPLICATIONS DESIGNATING THE U.S.					
PCT Application No.	PCT Filing Date	U.S. Serial Numbers Assigned (if any)			

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Frank J. Jordan Reg. No. 20,456
C. Bruce Hamburg Reg. No. 22,389

Herbert F. Ruschmann Reg. No. 35,341
Marvin Turken Reg. No. 18,330
Alfred D'Andrea Reg. No. 27,752

Send Correspondence To:

Jordan and Hamburg LLP
122 East 42nd Street
New York, New York 10168

Direct Telephone Calls to:
C. Bruce Hamburg
(212) 986-2340

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full Name of Sole or First Inventor	Inventor's Signature	Date
Klaus FISCHER	<i>Klaus Fischer</i>	30.07.07
Residence		Citizenship
Grillenbourg, Germany DEX		Germany
Post Office Address		
Frauensteiner Strasse 2, D-01737 Grillenburg, Germany		
Full Name of Second Joint Inventor, if any	Inventor's Signature	Date
Rainer SCHIENE	<i>Rainer Schiene</i>	31.07.07
Residence		Citizenship
Tharandt, Germany DEX		Germany
Post Office Address		
Weissiger Hoehe 3b, D-01737 Tharandt, Germany		
Full Name of Third Joint Inventor, if any	Inventor's Signature	Date
Joachim KATZUR	<i>Joachim Katzur</i>	6.08.07
Residence		Citizenship
Luebben, Germany DEX		Germany
Post Office Address		
Virchowstrasse 1a, D-03546 Luebben, Germany		